

KP25.2 Powerchair Script



Customer Details

Client					
Assessor					
Organisation					
	ACC		DSS		Other
User Weight					

Standard folding rear-wheel-drive powerchair; VR2 electronics; 50-amp batteries (2); 70-degree swingaway legrests; flip-up, height-adjustable armrests; anti-tips, pelvic positioning device, charger.

Seat Size (Width x Depth)

☐	14 x 16	☐	20 x 18
☐	16 x 16		
☐	16 x 18	☐	1" Seat extension rails & upholstery....\$
☐	18 x 16	☐	2" Seat extension rails & upholstery....\$
☐	18 x 18	Specify size: _____	

Controller

☐	Right hand side	Std
☐	Left hand side	\$
☐	Retractable controller arm	\$

Seat to Floor Height

☐	19"	Std
☐	21"	\$

Legrest Type

☐	70 Degree hangers	Std
☐	LHS ☐	RHS ☐
☐	90 Degree hangers	\$
☐	LHS ☐	RHS ☐
☐	Residual limb support	\$
☐	LHS ☐	RHS ☐
☐	Elevating legrests	\$
☐	LHS ☐	RHS ☐
☐	Extended legrest release lever	\$
☐	LHS ☐	RHS ☐

Footplates

☐	Standard footplate	Std
☐	Angle adjustable footplates	\$
☐	LHS ☐	RHS ☐
☐	Metal footplates	\$
☐	LHS ☐	RHS ☐

Anti-Tippers

☐	Standard double wheel	Std
--------------------------	-----------------------------	-----

Lower Leg Positioning

☐	Calf strap	Std
☐	Heel loops	\$
☐	LHS ☐	RHS ☐
☐	Foot strap	\$
☐	LHS ☐	RHS ☐

Backrest

☐	Standard upholstery	Std
☐	Tension adjustable	\$
☐	Backrest extension	\$
☐	Omit back upholstery	\$
☐	22" Back canes	\$

Backrest height required: _____

Optional Extras

☐	Tool kit and pump	Std
☐	Pelvic positioning belt (Plastic buckle)	Std
☐	Pelvic positioning belt (Auto buckle)	\$
☐	Perspex tray - Swing away	\$
☐	IV Pole	\$
☐	Oxygen bottle holder	\$
☐	Extension brake handle	\$
☐	LHS ☐	RHS ☐
☐	Curb climber	\$

Special Programming Instructions